NSN 5905-01-167-6975

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-167-6975 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.3120 inches Pilot Length: 0.1320 inches **Undercut Diameter:** 1.315 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 1.453 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.672 inches **Body Length:** 1.800 inches **Mounting Lip Diameter:** 1.4370 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 0.70 inch-ounces **Maximum Running Torque:** 0.70 inch-ounces **Shaft End Play:** 0.00500 inches

Shaft Runout: 0.001 inches

NSN 5905-01-167-6975

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Lateral Runoι	ut:
---------------	-----

0.002 inches

Pilot Diameter Runout:

0.00100 inches

Shaft Radial Play:

0.001 inches

Mechanical Backlash In Deg Angular Rotation:

0.041

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.000 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Resistance Tempurature Characteristic Range Per Section In Percent:

-5.0/+5.0 -65 degrees celsius all sections and -4.0/+4.0 -15 degrees celsius all sections and -2.5/+2.5 50 degrees celsius all sections and

-5.0/+5.0 75 degrees celsius all sections and -5.0/+5.0 105 degrees celsius all sections and -5.0/+5.0 125 degrees celsius all sections

Function Conformity Tolerance Per Section:

-0.10/+0.10 2nd section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Fixed Tap Quantity Per Section:

1 1st section

Tap Location Tolerance Per Section:

-250.0/+250.0 ohms 1st section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Stops

Tap Location From Ccw Terminal Per Section In Ohms:

2500.0 1st section

Function Characteristic Per Section:

All sections linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Special Features:

50kilohm load resistor on second section wiper

Unpackaged Unit Weight:

168.00 grams

NSN 5905-01-167-6975

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Test Data Document:

03538-7648736 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Typ	e And Quantity:
--------------	-----------------

7 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0