NSN 5905-01-167-8138

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-167-8138

Section Quantity:

| 1 | | |
|--|--|--|
| Body Style: | | |
| Cylindrical bushing mounted | | |
| Reliability Indicator: | | |
| Not established | | |
| Body Diameter: | | |
| 0.500 inches | | |
| Shaft Diameter: | | |
| 0.125 inches | | |
| Shaft Length: | | |
| 0.500 inches | | |
| Mounting Bushing Length: | | |
| 0.250 inches | | |
| Body Length: | | |
| 0.650 inches | | |
| Shaft Style: | | |
| Round, slotted | | |
| Actuator Type: | | |
| Single shaft | | |
| Effective Electrical Rotation In Deg Angular Rotation: | | |
| 300.0 | | |
| Maximum Starting Torque: | | |
| 6.00 inch-ounces | | |
| Maximum Running Torque: | | |
| 6.00 inch-ounces | | |
| Nonturn Device Location: | | |
| At 6 oclock | | |
| Nonturn Device Radius: | | |
| 0.187 inches | | |
| Screw Thread Diameter: | | |
| 0.250 inches | | |
| Screw Thread Series Designator: | | |
| Unef | | |
| Screw Thready Qty Per Inch (tpi): | | |
| 32.0 | | |
| Terminal Location: | | |
| Rear end | | |
| Mounting Method: | | |
| Standard bushing | | |
| Electrical Resistance Per Section: | | |
| 3.5 kilohms single section | | |

NSN 5905-01-167-8138

Precision Wire Wound Variable Resistor - Page 2 of 2



| Rotary Actuator | Travel In | Angular Deg: |
|------------------------|-----------|--------------|
|------------------------|-----------|--------------|

300.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-200.0/+200.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stone

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Test Data Document:

81349-mil-r-39002 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-r-39002/1 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0