NSN 5905-01-167-8455

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-167-8455

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Terminal Length:
Between 0.470 inches and 0.530 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
Between 0.100 inches and 0.130 inches
Shaft Length:
Between 0.036 inches and 0.080 inches
Body Length:
1.250 inches
Body Width:
0.190 inches
Body Height:
Between 0.300 inches and 0.330 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 7918.0 and 7922.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.900 inches
Fragility Factor:
Moderately rugged
Lateral Distance Between Mounting Hole Centers:
0.700 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Linthroaded halo

Unthreaded hole

NSN 5905-01-167-8455

Precision Wire Wound Variable Resistor - Page 2 of 2



Features Provided:
Humidity proof
Cubic Measure:
0.078 cubic inches
Electrical Resistance Per Section:
1.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 7918.0 and 7922.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.700 mils and 0.900 centimeters
Function Conformity Tolerance Per Section:
-0.20/+0.20 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70.0/+70.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0