

View Online at <https://aerobasegroup.com/nsn/5905-01-168-0710>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

Between 1.057 inches and 1.067 inches

Shaft Diameter:

Between 0.245 inches and 0.255 inches

Shaft Length:

Between 0.640 inches and 0.672 inches

Mounting Bushing Length:

Between 0.234 inches and 0.265 inches

Body Length:

1.750 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Switch Type:

Rotary

Actuator Type:

Single shaft

Switch Operating Position:

End of rotation

Switch Contact Arrangement:

Single pole, double throw, three positions maintained

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

Between 0.359 inches and 0.391 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Rear-bottom

Mounting Method:

Standard bushing

Features Provided:

Hermetically sealed and shaft seal and switch

Electrical Resistance Per Section:

5.0 percent, rated amperes c and better industrial clears

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 all sections

Actuator Travel Control Feature:

Stops

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0