Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-168-3224

# Section Quantity:

1

Body Style:

Rectangular

# Reliability Indicator:

Not established

# **Overall Length:**

0.447 inches

#### Terminal Length:

0.172 inches

#### **Overall Height:**

0.250 inches

#### **Overall Width:**

0.156 inches

#### Shaft Diameter:

0.062 inches

# Shaft Length:

0.050 inches

# Body Length:

0.250 inches

# Body Width:

0.156 inches

#### Body Height:

0.250 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

Between 5400.0 and 10800.0

## Maximum Starting Torque:

5.00 inch-ounces

## Maximum Running Torque:

5.00 inch-ounces

# Center To Center Distance Between Terminals:

0.200 inches

# Fragility Factor:

Moderately rugged

# **Terminal Location:**

Rear end

# Mounting Method:

Terminal

# NSN 5905-01-168-3224

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Features Provided:   |
|--|
| Humidity proof   |
| Electrical Resistance Per Section:   |
| 5.0 percent, rated amperes c and better flooring   |
| Rotary Actuator Travel In Angular Deg:   |
| Between 5400.0 and 10800.0   |
| Center To Center Distance Between Center Terminal And Outside Terminal:  |
| 0.100 inches   |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  |
| 150.0 single section   |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:  |
| -50.0/+50.0 single section   |
| Power Dissipation Rating Per Section In Watts:   |
| 0.375 7th secondary quality  |
| Resistance Tolerance Per Section In Percent:   |
| -5.0/+5.0 single section   |
| Actuator Travel Control Feature:   |
| Clutch   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  |
| 85.0 single section  |
| Standard Taper Curve Per Section:  |
| A single section   |
| Test Data Document:  |
| 81349-mil-r-27208 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Terminal Type And Quantity:  |
| 3 pin  |
| Specification Data:  |
| 81349-mil-r-27208/11 government specification  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A002a0   |
|  |
|  |