

View Online at https://aerobasegroup.com/nsn/5905-01-168-3226

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-10.0/+10.0

Electrical Resistance:

100.600 ohms

Resistance Tolerance In Percent:

-0.100/+0.100

Ambient Tempurature In Deg Celsius At Full Rated Power:

125.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

145.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-65.0/+145.0

Inclosure Method:

Encapsulated

Terminal Type:

Wire lead

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.010

Terminal Length:

1.500 inches

Body Diameter:

Between 0.235 inches and 0.265 inches

Body Length:

Between 0.468 inches and 0.520 inches

Power Dissipation Rating In Watts:

0.150 free air

Cubic Measure (non-core):

0.025 cubic inches

Style Designator:

Axial terminal each end

Test Data Document:

81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-39005/4 government specification

Shelf Life:

N/a

- Unit Of Measure:
- --
- Demilitarization:
- No

NSN 5905-01-168-3226

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig: A001a0