NSN 5905-01-169-1342

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/psp/5005-01-160-1342

view Online at https://aerobasegroup.com/nsn/5905-01-169-1542
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.890 inches
Body Diameter:
0.687 inches
Shaft Diameter:
0.125 inches
Shaft Length:
1.500 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.390 inches
Overall Diameter:
1.125 inches
Shaft Style:
Round
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
6.00 inch-ounces
Maximum Stop Torque:
72.00 inch-ounces
Nonturn Device Location:
At 3 oclock
Nonturn Device Radius:
0.234 inches
End Application:
Nimitz class cvn, los angeles class ssn (688), ticonderoga class cg (47), viginia class cgn (41), spruance class dd (963), sturgeon class
ssn (637), forrestal class cv, kidd class ddg, arleigh burke class ddg

0.250 inches

Screw Thread Diameter:

NSN 5905-01-169-1342

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.000 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
360.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+5.5 -55 degrees celsius single section and +0.0/+4.0 -40 degrees celsius single section and -2.5/+2.5 85 degrees celsius single
section and -3.0/+3.0 105 degrees celsius single section and -4.0/+4.0 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 7th secondary quality
Resistance Tolerance Per Section In Percent:
20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Criticality Code Justification:
Feat Feat
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Weapon system essential
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0