

View Online at <https://aerobasegroup.com/nsn/5905-01-169-2598>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.7500 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

1.080 inches

**Undercut Diameter:**

0.750 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

0.875 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.330 inches

**Body Length:**

0.750 inches

**Overall Diameter:**

0.875 inches

**Mounting Lip Diameter:**

0.8750 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

321.0

**Maximum Starting Torque:**

1.00 inch-ounces

**Maximum Running Torque:**

0.75 inch-ounces

**Maximum Stop Torque:**

32.00 inch-ounces

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

2.5 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

325.0

**Function Conformity Tolerance Per Section:**

-1.00/+1.00 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Terminal Type And Quantity:**

3 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0