

View Online at <https://aerobasegroup.com/nsn/5905-01-169-4103>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.100 inches

Shaft Length:

0.070 inches

Body Length:

1.250 inches

Body Width:

0.195 inches

Body Height:

0.320 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

7920.0

Maximum Starting Torque:

8.00 inch-ounces

Maximum Running Torque:

8.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Unthreaded hole

Cubic Measure:

0.078 cubic inches

Electrical Resistance Per Section:

50.000 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

7920.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire loop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0