## NSN 5905-01-169-9932

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-169-9932 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.289 inches **Body Diameter:** 0.391 inches **Shaft Diameter:** 0.126 inches **Shaft Length:** 0.630 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.469 inches **Overall Diameter:** 0.391 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 280.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0

Terminal Location:
Rear end

Mounting Method: Standard bushing

## NSN 5905-01-169-9932

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
100.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
280.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire loop
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0