NSN 5905-01-173-4320

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-173-4320

-20.0/+20.0 first temp coefficient

Electrical Resistance:

75.000 ohms

Resistance Tolerance In Percent:

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

25.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+275.0 temp range of first temp coefficient

Inclosure Method:

Encapsulated

Terminal Type:

Wire lead

Reactance Characteristic:

Inductive

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.001

Terminal Length:

1.500 inches

Body Diameter:

Between 0.063 inches and 0.125 inches

Body Length:

Between 0.375 inches and 0.437 inches

Power Dissipation Rating In Watts:

2.000 free air

Special Features:

Nuclear hardness critical items

Nuclear Hardness Critical Feature:

Hardened

Style Designator:

Axial terminal each end

Test Data Document:

81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-39007/8 government specification

Shelf Life:

N/a

NSN 5905-01-173-4320

Inductive Wire Wound Fixed Resistor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0