## NSN 5905-01-173-9044

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-173-9044

-5.0/45.0 Electrical Resistance: 141.746 kilohms Resistance Tolerance In Percent: -0.025/40.025 Ambient Tempurature In Deg Celsius At Full Rated Power: 85.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -2.00/48.5.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.000 inches Body Diameter: -0.102 inches Body Diameter: -0.102 inches Power Dissipation Rating In Watts: -0.100 free air End Application: 2strius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv., oliver perry class fig. kilotue dass t-ae 26, whidbey island class lsd., general purpose electronic test equipment (gpete). Style Designator:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 141.748 kilohms Resistance Tolerance In Percent: -0.026/40.025 Ambient Tempurature In Deg Celsius At Full Rated Power: 85.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.000 inches Body Length: -0.300 inches Power Dissipation Rating In Watts: -0.102 inches Power Dissipation Rating In Watts: -0.103 inches Power Dissipation Rating In Watts: -0.104 inches Shody beginnator: -2strius class 1-ae 26, whichey island class lad, general purpose electronic test equipment (gpete). Style Designator:	-5.0/+5.0
Resistance Tolerance In Percent: -0.025/+0.025 Ambient Tempurature In Deg Celsius At Full Rated Power: 85.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.1012 inches Body Diameter: 0.1020 inches Body Length: 0.300 inches Power Dissipation Rating In Watts: 0.100 free air End Application: 2sirius class 1-afs 8, spruance class dd (953), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class 1-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete). Style Designator: Avial terminal each end Sheft Life: IVa Unit Of Measure:	Electrical Resistance:
-0.025/40.025 Ambient Tempurature In Deg Celsius At Full Rated Power: 85.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.102 inches Body Diameter: 0.102 inches Body Length: 0.300 inches Power Dissipation Rating In Watts: 0.100 free air End Application: 2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class isd, general purpose electronic test equipment (gpete). Style Designator: Axial terminal each end Sheff Life: Na Unit Of Measure:	141.746 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 85.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 155.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.102 inches Body Length: 0.300 inches Power Dissipation Rating In Watts: 0.100 free air End Application: 2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class isd. general purpose electronic test equipment (gpete). Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  20.0/+85.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.000 inches  Body Diameter:  0.102 inches  Body Diameter:  0.300 inches  Power Dissipation Rating In Watts:  0.100 free air  End Application:  2sirius class t-ae 28, whidbey island class Isd, general purpose electronic test equipment (gpete).  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:  —  Demilitarization:  No  Flig:	-0.025/+0.025
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+85.0  Incicosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 1.000 inches  Body Diameter: 0.102 inches  Body Length: 0.300 inches  Body Length: 0.300 inches  Power Dissipation Rating In Watts: 0.100 free air  End Application: 2sirius class t-ae 26, whidbey island class Isd, general purpose electronic test equipment (gpete).  Style Designator: Axial terminal each end  Sheff Life: N/a  Unit Of Measure: Demilitarization: No  Fiig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.04-95.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.102 inches Body Length: 0.300 inches Power Dissipation Rating in Watts: 0.100 fee air End Application: Seliuse class t-as 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete). Style Designator: Axial terminal each end Sheft Life: N/a Unit Of Measure: Demilitarization: No Flig:	85.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.102 inches Body Length: 0.300 inches Power Dissipation Rating In Watts: 0.100 free air End Application: 2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete). Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-20.0/+85.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.102 inches Body Length: 0.300 inches Power Dissipation Rating In Watts: 0.300 inches Power Dissipation Rating In Watts: 0.100 free air End Application: 2sirius class t-as 8, spruance class dd (963), austin ship class [pd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class Isd, general purpose electronic test equipment (gpete). Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	150.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.102 inches Body Length: 0.300 inches Power Dissipation Rating In Watts: 0.100 free air End Application: 2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv. oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete). Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.102 inches Body Length: 0.300 inches Power Dissipation Rating In Watts: 0.100 free air End Application: 2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete). Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-20.0/+85.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.000 inches  Body Diameter:  0.102 inches  Body Length:  0.300 inches  Power Dissipation Rating In Watts:  0.100 free air  End Application:  2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Terminal Length: 1.000 inches  Body Diameter: 0.102 inches  Body Length: 0.300 inches  Power Dissipation Rating In Watts: 0.100 free air  End Application: 2 sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Flig:	Encapsulated
Reliability Indicator:  Not established  Terminal Length:  1.000 inches  Body Diameter:  0.102 inches  Body Length:  0.300 inches  Power Dissipation Rating In Watts:  0.100 free air  End Application:  2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:  —  Demilitarization:  No  Fig:	Terminal Type:
Note stablished Terminal Length: 1.000 inches Body Diameter: 0.102 inches Body Length: 0.300 inches Power Dissipation Rating In Watts: 0.100 free air End Application: 2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete). Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Wire lead
Terminal Length:  1.000 inches  Body Diameter:  0.102 inches  Body Length:  0.300 inches  Power Dissipation Rating In Watts:  0.100 free air  End Application:  2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Reliability Indicator:
1.000 inches  Body Diameter: 0.102 inches  Body Length: 0.300 inches  Power Dissipation Rating In Watts: 0.100 free air  End Application: 2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator: Axial terminal each end  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Not established
Body Diameter:  0.102 inches  Body Length: 0.300 inches  Power Dissipation Rating In Watts: 0.100 free air  End Application: 2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator: Axial terminal each end  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Terminal Length:
0.102 inches  Body Length: 0.300 inches  Power Dissipation Rating In Watts: 0.100 free air  End Application: 2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	1.000 inches
Body Length:  0.300 inches  Power Dissipation Rating In Watts:  0.100 free air  End Application:  2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Diameter:
0.300 inches  Power Dissipation Rating In Watts: 0.100 free air  End Application: 2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator: Axial terminal each end  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.102 inches
Power Dissipation Rating In Watts:  0.100 free air  End Application:  2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Length:
End Application:  2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.300 inches
End Application: 2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator:  Axial terminal each end  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Power Dissipation Rating In Watts:
2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg, kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.100 free air
kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	End Application:
Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	2sirius class t-afs 8, spruance class dd (963), austin ship class lpd-4 amphibious transport docks, forrestal class cv, oliver perry class ffg.
Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	kilauea class t-ae 26, whidbey island class lsd, general purpose electronic test equipment (gpete).
Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0