NSN 5905-01-174-2259

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-174-2259

Section Quantity: Body Style: Rectangular **Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Stud Length:** 0.375 inches **Body Length:** 1.425 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **End Application:** E-2c acft; aircraft, c-2a (reprocured); fms-aircraft, hawkeye e-2c **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Terminal Location:** Right adjacent side two rows **Mounting Method:** Threaded stud

Electrical Resistance Per Section:

2.5 kilohms all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

NSN 5905-01-174-2259

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0