Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-174-5377

# Section Quantity:

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

#### **Terminal Length:**

0.200 inches

**Body Length:** 

0.190 inches

**Body Width:** 

#### 0.375 inches

Body Height:

0.375 inches

#### Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

310.0

### Maximum Starting Torque:

5.00 inch-ounces

#### Maximum Running Torque:

5.00 inch-ounces

# Center To Center Distance Between Terminals:

0.200 inches

#### **Terminal Location:**

Rear end

#### Mounting Method:

Terminal

### Cubic Measure:

0.027 cubic inches

#### **Electrical Resistance Per Section:**

20.000 ohms single section

### **Rotary Actuator Travel In Angular Deg:**

310.0

### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

#### **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section



**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

## Actuator Travel Control Feature:

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Unpackaged Unit Weight:

0.84 grams

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0