NSN 5905-01-174-5603

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-174-5603

Section Quantity						
Section Quantity:						
1 Padu Studa						
Body Style:						
Rectangular						
Reliability Indicator:						
Not established						
Terminal Length:						
0.300 inches						
Shaft Diameter:						
0.085 inches						
Shaft Length:						
0.050 inches						
Body Length:						
0.410 inches						
Body Width:						
0.150 inches						
Body Height:						
0.375 inches						
Shaft Style:						
Round, slotted						
Actuator Type:						
Single shaft						
Maximum Starting Torque:						
5.00 inch-ounces						
Maximum Running Torque:						
5.00 inch-ounces						
Center To Center Distance Between Terminals:						
0.200 inches						
Terminal Location:						
Rear end						
Mounting Method:						
Terminal						
Electrical Resistance Per Section:						
100.000 ohms single section						
Center To Center Distance Between Center Terminal And Outside Terminal:						
0.100 inches						
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:						
150.0 single section						
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:						
-100.0/+100.0 single section						

0.5 free air single section

Power Dissipation Rating Per Section In Watts:

NSN 5905-01-174-5603

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



R	esistance	Tolerance	Per 9	Section	In	Percent:
◥	esisiance	i olei alice	rei .	Section		reiteiit.

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0