NSN 5905-01-174-5606

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-174-5606

One them Overwitten
Section Quantity:
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.300 inches
Shaft Diameter:
0.085 inches
Shaft Length:
0.050 inches
Body Length:
0.410 inches
Body Width:
0.150 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
1.000 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section

0.5 free air single section

Power Dissipation Rating Per Section In Watts:

NSN 5905-01-174-5606

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance	Tolerance	Per	Section	In	Percent:

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0