NSN 5905-01-175-0705

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-175-0705

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0 to 100.0

Electrical Resistance:

43.000 kilohms

Resistance Tolerance In Percent:

-2.000 to 2.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 150.0

Inclosure Method:

Encapsulated

Terminal Type:

Wire lead

Mil-std-1276 Wire Lead Type Designator:

С

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.001

Terminal Length:

Between 1.000 inches and 1.625 inches

Body Diameter:

Between 0.058 inches and 0.074 inches

Body Length:

Between 0.130 inches and 0.187 inches

Power Dissipation Rating In Watts:

0.125 free air

Nuclear Hardness Critical Feature:

Hardened

Unpackaged Unit Weight:

0.3 grams

Style Designator:

Axial terminal each end

Test Data Document:

81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-39017/5 government specification

Shelf Life:

NSN 5905-01-175-0705

Film Fixed Resistor - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A001a0

