

View Online at <https://aerobasegroup.com/nsn/5905-01-175-4452>

**Temperature Coefficient Of Resistance In Ppm Per Deg Celsius:**

-20.0/+20.0 second temp coefficient

**Electrical Resistance:**

30.100 kilohms highest resistance value

**Resistance Tolerance In Percent:**

-1.000/+1.000 each resistor

**Ambient Temperature In Deg Celsius At Full Rated Power:**

25.0

**Ambient Temperature In Deg Celsius At Zero Percent Rated Power:**

275.0

**Temperature Range Of Temperature Coefficient In Deg Celsius:**

-55.0/+275.0 temp range of first temp coefficient

**Inclosure Method:**

Encapsulated

**Terminal Type:**

Wire lead

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.001

**Terminal Length:**

1.500 inches

**Body Diameter:**

0.375 inches

**Body Length:**

1.780 inches

**Power Dissipation Rating In Watts:**

10.000 free air

**Unpackaged Unit Weight:**

13.000 grams

**Style Designator:**

Axial terminal each end

**Test Data Document:**

81349-mil-prf-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-prf-39007/7 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A001a0

**Mil-std (military Standard):**

Mil-prf-39007 spec.