NSN 5905-01-175-5667

Section Quantity:

Cylindrical servo mounted **Reliability Indicator:**

Between 0.4995 inches and 0.5000 inches

Body Style:

Not established Pilot Diameter:

Pilot Length: 0.0630 inches

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-175-5667

First Flat Length:
0.375 inches
Flat Height:
0.066 inches
Undercut Diameter:
Between 0.615 inches and 0.625 inches
Undercut Width:
0.0620 inches
Shaft Diameter:
Between 0.1243 inches and 0.1248 inches
Shaft Length:
Between 0.610 inches and 0.640 inches
Body Length:
0.660 inches
Mounting Lip Diameter:
Between 0.6150 inches and 0.6250 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Terminal Location:
Right adjacent side single row
Mounting Method:
Shaft
Electrical Resistance Per Section:
5.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.7 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section

NSN 5905-01-175-5667

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
1 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0