## NSN 5905-01-175-6063

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-175-6063 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.562 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.344 inches **Actuator Type:** Recessed drive with slot **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 50.0 kilohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -15.0/+15.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5905-01-175-6063

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0