

View Online at https://aerobasegroup.com/nsn/5905-01-176-5021

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Overall Length:
0.472 inches
Terminal Length:
0.172 inches
Overall Height:
0.250 inches
Overall Width:
0.165 inches
Shaft Diameter:
0.075 inches
Shaft Length:
0.050 inches
Body Length:
0.250 inches
Body Width:
0.165 inches
Body Height:
0.250 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 3600.0 and 9000.0
Maximum Starting Torque:
3.00 inch-ounces
Maximum Running Torque:
3.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Rear end

NSN 5905-01-176-5021 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:	
Terminal	
Cubic Measure:	
0.010 cubic inches	
Electrical Resistance	Per Section:
20.000 percent, rated	amperes c and better flooring
Rotary Actuator Trav	el In Angular Deg:
Between 3600.0 and 9	000.0
Center To Center Dis	ance Between Center Terminal And Outside Terminal:
0.100 inches	
Ambient Tempurature	e In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section	
Tempurature Coeffici	ent Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single se	ection
Power Dissipation Ra	ting Per Section In Watts:
0.25 7th secondary qua	ality
Resistance Tolerance	Per Section In Percent:
-10.0/+10.0 single sect	ion
Actuator Travel Cont	rol Feature:
Clutch	
Ambient Tempurature	e In Deg Celsius Per Section At Full Rated Power:
85.0 single section	
Standard Taper Curve	e Per Section:
A single section	
Test Data Document:	
81349-mil-r-39035 spe	cification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificatio
format; excludes comr	nercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and per	formance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Q	uantity:
3 pin	
Specification Data:	
81349-mil-r-39035/3 g	overnment specification
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A002a0	