NSN 5905-01-176-5512

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-176-5512

View Online at https://aerobasegroup.com/nsn/5905-01-176-5512
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-5.0/+5.0
Electrical Resistance:
1.000 kilohms
Resistance Tolerance In Percent:
-0.010/+0.010
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
145.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-65.0/+145.0
Inclosure Method:
Encapsulated
Terminal Type:
Tab, solder lug
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
1.000 inches
Body Diameter:
0.160 inches
Body Length:
0.325 inches
Power Dissipation Rating In Watts:
0.100 free air
Terminal Width:
0.020 inches
Cubic Measure (non-core):
0.007 cubic inches
Unpackaged Unit Weight:
0.400 grams
Style Designator:
Radial terminal each end
Test Data Document:
81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-39005/11 government specification

N/a

Shelf Life:

NSN 5905-01-176-5512

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0