

View Online at <https://aerobasegroup.com/nsn/5905-01-176-5657>

Reliability Indicator:

Not established

Terminal Surface Treatment:

Solder

Terminal Length:

1.500 inches

Body Outside Diameter:

0.440 inches

Body Width:

0.360 inches

Terminal Diameter:

0.025 inches

Maximum Power Dissipation Rating:

1.00 watts

Ambient Temperature At Full Rated Power:

25.0 degrees celsius

Maximum Operating Temp:

125.0 degrees celsius

Thermal Time Constant In Seconds:

250.0

Power Dissipation Constant In Milliwatts Per Deg Celsius:

10.0

Temperature Points For Resistance Readings At Zero Power:

75.0 degrees celsius 6th resistance-temperature point

Zero Power Resistance At Specificationified Temp:

9.4 ohms 6th resistance-temperature point

Resistance Tolerance At A Specificationified Temperature In Percent:

-9.0/+9.0 6th resistance-temperature point

Inclosure Type:

Encapsulated

Cubic Measure:

0.034 cubic inches

Zero Power Resistance:

51.000 ohms

Zero Power Resistance Tolerance In Percent At Reference Temp:

-5.0/+5.0

Reference Temperature In Deg Celsius:

25.0

Unpackaged Unit Weight:

0.500 grams

Style Designator:

Spherical

Test Data Document:

81349-mil-r-23648 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 wire lead

Specification Data:

81349-mil-r-23648/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A086a0