Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-176-7152

### Section Quantity:

1

Body Style:

Cylindrical servo mounted

## **Reliability Indicator:**

Not established

### **Pilot Diameter:**

0.6250 inches

#### **Pilot Length:**

0.0620 inches

### **Overall Length:**

1.588 inches

### **Undercut Diameter:**

0.781 inches

#### **Undercut Width:**

### 0.0620 inches

**Body Diameter:** 

0.875 inches

### Shaft Diameter:

0.1248 inches

### Shaft Length:

0.375 inches

### Body Length:

1.213 inches

### **Overall Diameter:**

1.250 inches

### Mounting Lip Diameter:

0.8750 inches

### Mounting Lip Depth:

0.0620 inches

### Shaft Style:

Round

# Shaft Bearing Type:

Ball

### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

1800.0

### Maximum Starting Torque:

0.40 inch-ounces

### Maximum Running Torque:

0.40 inch-ounces

AeroBase Group

### Maximum Stop Torque:

128.00 inch-ounces

#### Shaft End Play:

0.00500 inches

### Shaft Runout:

0.001 inches

# Lateral Runout:

0.003 inches

#### Pilot Diameter Runout:

0.00150 inches

### Shaft Radial Play:

0.002 inches

### **Terminal Location:**

Longitudinally positioned on the circumference

#### **Mounting Method:**

Clamp ring

### **Electrical Resistance Per Section:**

2.000 percent, rated amperes c and better flooring

### **Rotary Actuator Travel In Angular Deg:**

1800.0

#### **Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0/+70.0 single section

### **Power Dissipation Rating Per Section In Watts:**

1.5 7th secondary quality

# Function Conformity Per Section:

Single section independent linearity

## Fixed Tap Quantity Per Section:

1 single section

# Tap Location Tolerance Per Section:

-20.0/+20.0 ohms single section

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# Actuator Travel Control Feature:

Stops

### Tap Location From Ccw Terminal Per Section In Ohms:

1000.0 single section

### **Function Characteristic Per Section:**

7 oclock all primaries

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section



# Test Data Document:

58260-13084177 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0