NSN 5905-01-176-9306

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-176-9306

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0 first temp coefficient

Electrical Resistance:

1.600 kilohms

Resistance Tolerance In Percent:

-2.000/+2.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+150.0 temp range of first temp coefficient

Inclosure Method:

Encapsulated

Terminal Type:

Wire lead

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.001

Terminal Length:

1.250 inches

Body Diameter:

0.066 inches

Body Length:

0.150 inches

Power Dissipation Rating In Watts:

0.125 free air

Style Designator:

Axial terminal each end

Test Data Document:

81349-mil-prf-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-prf-39017/5 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A001a0

NSN 5905-01-176-9306

Film Fixed Resistor - Page 2 of 2

Mil-std (military Standard):

Mil-prf-39017 spec.

