Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-177-9474

Section Quantity:

1

Body Style:

Cylindrical hole/slot mounted

Reliability Indicator:

Not established

First Flat Length:

1.500 inches

Flat Height:

0.344 inches

Body Diameter:

5.090 inches

Shaft Diameter:

0.375 inches

Shaft Length:

2.000 inches

Body Length:

2.160 inches

Mounting Hole/stud Circle Diameter:

1.750 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

310.0

Maximum Starting Torque:

160.00 inch-ounces

Maximum Running Torque:

160.00 inch-ounces

Maximum Stop Torque:

240.00 inch-ounces

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

20.0

Mounting Facility Quantity:

2



Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Electrical Resistance Per Section:

50.0 ohms single section

Rotary Actuator Travel In Angular Deg:

310.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

390.0 single section

Power Dissipation Rating Per Section In Watts:

225.0 heat sink single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-r-22/10 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0