Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-178-0846

## Section Quantity:

1

Body Style:

Rectangular bushing mounted

# Reliability Indicator:

Not established

## **Terminal Length:**

0.500 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

#### Body Length:

## 0.625 inches

Body Width:

0.625 inches

# Body Height:

0.625 inches

# Shaft Style:

Round

# Shaft Bearing Type:

Sleeve

# Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

260.0

# Maximum Starting Torque:

2.50 inch-ounces

# Maximum Running Torque:

2.50 inch-ounces

# Maximum Stop Torque:

64.00 inch-ounces

# Center To Center Distance Between Terminals:

0.200 inches

# Fragility Factor:

Moderately rugged

# End Application:

Support equipment f-4, ov-10a, c-5, t-37, h-53, f-16, b-52 acft

# Screw Thread Diameter:

0.250 inches

# NSN 5905-01-178-0846

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side two rows

#### **Mounting Method:**

Standard bushing

## Center To Center Distance Between Terminal Rows:

0.200 inches

**Features Provided:** 

Humidity proof

Cubic Measure:

0.254 cubic inches

**Electrical Resistance Per Section:** 

50.000 kilohms single section

## **Rotary Actuator Travel In Angular Deg:**

300.0

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

## Resistance Tempurature Characteristic Range Per Section In Percent:

+0.0/+7.0 -55 degrees celsius single section and +0.0/+3.5 -25 degrees celsius single section and -2.5/+2.5 85 degrees celsius single

section and +0.0/+5.5 120 degrees celsius single section

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

## **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## Actuator Travel Control Feature:

Stops

## **Criticality Code Justification:**

Feat

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

# Standard Taper Curve Per Section:

A single section

# **Special Features:**

Weapon system essential

# Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

- Unit Of Measure:
- --

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0