NSN 5905-01-179-6636

Non-wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-01-179-6636



Section Quantity: 2 First Flat Length: 0.400 inches Flat Height: 0.094 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.041 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Actuator Type:** Single shaft **Maximum Starting Torque:** 6.00 inch-ounces **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Locking bushing **Power Dissipation Rating Per Section In Watts:** 0.2 free air single section **Function Conformity Per Section:** Single section independent linearity **Fixed Tap Quantity Per Section:** 3 single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 all sections

A single section

Standard Taper Curve Per Section:

NSN 5905-01-179-6636

Non-wire Wound Variable Resistor - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0