NSN 5905-01-179-9429

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-179-9429

Townson Coefficient Of Bosiston on In Daw Boy Coloins				
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:				
-50.0/+50.0				
Electrical Resistance:				
4.640 ohms				
Resistance Tolerance In Percent:				
-1.000/+1.000				
Ambient Tempurature In Deg Celsius At Full Rated Power:				
25.0				
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:				
275.0				
Tempurature Range Of Tempurature Coefficient In Deg Celsius:				
-55.0/+275.0				
Inclosure Method:				
Encapsulated				
Terminal Type:				
Tab, solder lug				
Reactance Characteristic:				
Inductive				
Reliability Indicator:				
Established				
Reliability Failure Rate Level In Percent:				
1.000				
Tarminal Langth:				
Terminal Length:				
0.312 inches				
-				
0.312 inches				
0.312 inches Body Length:				
0.312 inches Body Length: 0.750 inches				
0.312 inches Body Length: 0.750 inches Body Width:				
0.312 inches Body Length: 0.750 inches Body Width: 0.438 inches				
0.312 inches Body Length: 0.750 inches Body Width: 0.438 inches Body Height:				
0.312 inches Body Length: 0.750 inches Body Width: 0.438 inches Body Height: 0.406 inches				
0.312 inches Body Length: 0.750 inches Body Width: 0.438 inches Body Height: 0.406 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:				
0.312 inches Body Length: 0.750 inches Body Width: 0.438 inches Body Height: 0.406 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.562 inches				
0.312 inches Body Length: 0.750 inches Body Width: 0.438 inches Body Height: 0.406 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.562 inches Power Dissipation Rating In Watts:				
0.312 inches Body Length: 0.750 inches Body Width: 0.438 inches Body Height: 0.406 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.562 inches Power Dissipation Rating In Watts: 6.000 free air				
0.312 inches Body Length: 0.750 inches Body Width: 0.438 inches Body Height: 0.406 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.562 inches Power Dissipation Rating In Watts: 6.000 free air Terminal Width:				
0.312 inches Body Length: 0.750 inches Body Width: 0.438 inches Body Height: 0.406 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.562 inches Power Dissipation Rating In Watts: 6.000 free air Terminal Width: 0.140 inches				
Body Length: 0.750 inches Body Width: 0.438 inches Body Height: 0.406 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.562 inches Power Dissipation Rating In Watts: 6.000 free air Terminal Width: 0.140 inches Mounting Hole Size:				
0.312 inches Body Length: 0.750 inches Body Width: 0.438 inches Body Height: 0.406 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.562 inches Power Dissipation Rating In Watts: 6.000 free air Terminal Width: 0.140 inches Mounting Hole Size: 0.094 inches				

N/a

NSN 5905-01-179-9429

Wire Wound Fixed Resistor - Page 2 of 2



U	nit	Of	Measure:

--

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-r-39009 spec.