Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-180-7888

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.060 inches

Shaft Length:

0.035 inches

Body Length:

0.500 inches

Body Width:

0.187 inches

Body Height:

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

15120.0

Maximum Starting Torque:

7.50 inch-ounces

Maximum Running Torque:

3.50 inch-ounces

Lateral Distance Between Mounting Hole Centers:

0.520 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Unthreaded hole

Cubic Measure:

0.047 cubic inches

Electrical Resistance Per Section:

30.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

15120.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 7th secondary quality **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 50.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0