NSN 5905-01-181-8956

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-181-8956 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.452 inches **Body Diameter:** 2.810 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 1.780 inches **Overall Diameter:** 3.640 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 310.0 **Maximum Starting Torque:** 4.00 inch-ounces **Maximum Running Torque:** 4.00 inch-ounces **Maximum Stop Torque:** 240.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef

Screw Thready Qty Per Inch (tpi):

32.0

NSN 5905-01-181-8956

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Locking bushing
Features Provided:
Shaft locking device
Electrical Resistance Per Section:
15.0 ohms single section
Rotary Actuator Travel In Angular Deg:
310.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
75.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-22/7 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0
\002a0