

View Online at <https://aerobasegroup.com/nsn/5905-01-182-1617>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.4375 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

0.965 inches

**Undercut Diameter:**

0.4375 inches

**Undercut Width:**

0.0570 inches

**Body Diameter:**

0.500 inches

**Shaft Diameter:**

0.1248 inches

**Shaft Length:**

0.330 inches

**Body Length:**

0.535 inches

**Mounting Lip Diameter:**

0.5000 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Maximum Starting Torque:**

75.00 inch-ounces

**Maximum Running Torque:**

75.00 inch-ounces

**Terminal Location:**

Rear end

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Function Conformity Tolerance Per Section:**

-1.00/+1.00 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Function Characteristic Per Section:**

Single section linear

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Special Features:**

Shaft has 0.039 inch diameter through hole located 0.070 inches from end of shaft

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0