NSN 5905-01-182-1622

Hybrid Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-182-1622

Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.312 inches
Body Diameter:
0.875 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.812 inches
Mounting Bushing Length:
0.312 inches
Body Length:
1.500 inches
Overall Diameter:
1.250 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
1.60 inch-ounces
Maximum Running Torque:
1.60 inch-ounces
Maximum Stop Torque:
60.00 inch-ounces
Shaft End Play:
0.010 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.004 inches
Pilot Diameter Runout:
0.004 inches
Shaft Radial Play:

0.002 inches

NSN 5905-01-182-1622

Hybrid Variable Resistor - Page 2 of 2



Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.0 percent, rated amperes c and better
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-150.0/+100.0 all sections
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary at 10'30 oclock
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
6 oclock all primaries
·
Terminal Type And Quantity:
•
Unit Of Measure:
Demilitarization:
A002a0
All sections independent linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 all sections Actuator Travel Control Feature: Stops Function Characteristic Per Section: 6 oclock all primaries Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Terminal Type And Quantity: 6 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: