NSN 5905-01-182-3197

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-182-3197 **Section Quantity:** 2 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Terminal Length:** 0.170 inches **Shaft Diameter:** 0.118 inches **Shaft Length:** 0.492 inches **Mounting Bushing Length:** 0.276 inches **Body Length:** 0.394 inches **Body Width:** 0.394 inches **Body Height:** 0.394 inches **Shaft Style:** Round Switch Type: Rotary **Switch Voltage Rating In Volts:** 17.0 **Actuator Type:** Single shaft **Switch Operating Position:** End of rotation **Switch Contact Arrangement:** Single pole, single throw, normally open, both positions maintained **Center To Center Distance Between Terminals:** 0.200 inches **Screw Thread Diameter:** 0.276 inches **Screw Thread Series Designator:** Iso m Screw Thready Qty Per Inch (tpi):

34.0

Terminal Location:

Lower adjacent side single row

NSN 5905-01-182-3197

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
22.000 kilohms all sections
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 all sections
Power Dissipation Rating Per Section In Watts:
0.1 free air all sections
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Switch Current Type And Rating In Amps:
0.400 dc
Terminal Type And Quantity:
6 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0