NSN 5905-01-182-8156

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-182-8156

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.200 inches
Body Length:
0.140 inches
Body Width:
0.375 inches
Body Height:
0.375 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
280.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inch as
0.300 inches
Terminal Location:
Terminal Location:
Terminal Location: Lower adjacent side single row
Terminal Location: Lower adjacent side single row Mounting Method:
Terminal Location: Lower adjacent side single row Mounting Method: Terminal
Terminal Location: Lower adjacent side single row Mounting Method: Terminal Cubic Measure:
Terminal Location: Lower adjacent side single row Mounting Method: Terminal Cubic Measure: 0.020 cubic inches
Terminal Location: Lower adjacent side single row Mounting Method: Terminal Cubic Measure: 0.020 cubic inches Electrical Resistance Per Section:
Terminal Location: Lower adjacent side single row Mounting Method: Terminal Cubic Measure: 0.020 cubic inches Electrical Resistance Per Section: 20.000 percent, rated amperes c and better flooring
Terminal Location: Lower adjacent side single row Mounting Method: Terminal Cubic Measure: 0.020 cubic inches Electrical Resistance Per Section: 20.000 percent, rated amperes c and better flooring Rotary Actuator Travel In Angular Deg:
Terminal Location: Lower adjacent side single row Mounting Method: Terminal Cubic Measure: 0.020 cubic inches Electrical Resistance Per Section: 20.000 percent, rated amperes c and better flooring Rotary Actuator Travel In Angular Deg: 310.0
Terminal Location: Lower adjacent side single row Mounting Method: Terminal Cubic Measure: 0.020 cubic inches Electrical Resistance Per Section: 20.000 percent, rated amperes c and better flooring Rotary Actuator Travel In Angular Deg: 310.0 Center To Center Distance Between Center Terminal And Outside Terminal:
Terminal Location: Lower adjacent side single row Mounting Method: Terminal Cubic Measure: 0.020 cubic inches Electrical Resistance Per Section: 20.000 percent, rated amperes c and better flooring Rotary Actuator Travel In Angular Deg: 310.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.150 inches
Terminal Location: Lower adjacent side single row Mounting Method: Terminal Cubic Measure: 0.020 cubic inches Electrical Resistance Per Section: 20.000 percent, rated amperes c and better flooring Rotary Actuator Travel In Angular Deg: 310.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.150 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

0.5 7th secondary quality

Power Dissipation Rating Per Section In Watts:

NSN 5905-01-182-8156

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No