# NSN 5905-01-183-9254

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-183-9254

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-30.0/+30.0
Electrical Resistance:
15.800 kilohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
Encapsulated
Terminal Type:
Tab, solder lug
Reactance Characteristic:
Inductive
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
Reliability Failure Rate Level In Percent: 0.010
0.010
0.010 Terminal Length:
0.010 Terminal Length: 0.438 inches
0.010 Terminal Length: 0.438 inches Body Length:
0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches
0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width:
0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches
0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height:
0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches
0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.010 Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches
Terminal Length: 0.438 inches  Body Length: 1.938 inches  Body Width: 0.594 inches  Body Height: 0.625 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches  Power Dissipation Rating In Watts:
Terminal Length: 0.438 inches Body Length: 1.938 inches Body Width: 0.594 inches Body Height: 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches Power Dissipation Rating In Watts: 10.000 free air
Terminal Length: 0.438 inches  Body Length: 1.938 inches  Body Width: 0.594 inches  Body Height: 0.625 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.562 inches  Power Dissipation Rating In Watts: 10.000 free air  Terminal Width:
Terminal Length:  0.438 inches  Body Length:  1.938 inches  Body Width:  0.594 inches  Body Height:  0.625 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:  1.562 inches  Power Dissipation Rating In Watts:  10.000 free air  Terminal Width:  0.140 inches
Terminal Length:  0.438 inches  Body Length:  1.938 inches  Body Width:  0.594 inches  Body Height:  0.625 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:  1.562 inches  Power Dissipation Rating In Watts:  10.000 free air  Terminal Width:  0.140 inches  Mounting Hole Size:
Terminal Length:  0.438 inches  Body Length:  1.938 inches  Body Width:  0.594 inches  Body Height:  0.625 inches  Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:  1.562 inches  Power Dissipation Rating In Watts:  10.000 free air  Terminal Width:  0.140 inches  Mounting Hole Size:  0.125 inches

32.000 grams

## NSN 5905-01-183-9254

Wire Wound Fixed Resistor - Page 2 of 2



### **Style Designator:**

Axial terminal (s)

### **Test Data Document:**

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-r-39009/1 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A001a0