NSN 5905-01-184-0884

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-184-0884 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.561 inches **Body Diameter:** 1.156 centimeters **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.250 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.312 inches **Overall Diameter:** 1.750 inches **Undercut Diameter:** 0.125 inches **Shaft Style:** Round, stepped **Shaft Bearing Type:** Sleeve **Actuator Type:** Dual concentric **Effective Electrical Rotation In Deg Angular Rotation:** 292.0 **Maximum Starting Torque:** 9.00 inch-ounces **Maximum Running Torque:** 9.00 inch-ounces **Maximum Stop Torque:** 192.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:**

0.531 inches

Fragility Factor:

ragility ractor.

Moderately rugged

NSN 5905-01-184-0884

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Undercut Length:
0.375 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Cubic Measure:
1.312 cubic inches
Electrical Resistance Per Section:
10.000 percent, rated amperes c and better
Rotary Actuator Travel In Angular Deg:
312.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+7.0 -55 degrees celsius all sections and +0.0/+3.5 -25 degrees celsius all sections and +0.0/+2.0 0 degrees celsius all sections and
2.5/+2.5 85 degrees celsius all sections and +0.0/+5.5 120 degrees celsius all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 all sections
Power Dissipation Rating Per Section In Watts:
2.25 7th secondary at 10'30 oclock
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No