NSN 5905-01-184-1441

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-184-1441

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
0.940 inches
First Flat Length:
0.160 inches
Flat Height:
0.109 inches
Body Diameter:
0.688 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.440 inches
Mounting Bushing Length:
0.200 inches
Body Length:
0.500 inches
Overall Diameter:
1.120 inches
Shaft Style:
Round, flatted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 251.0 and 318.0
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
6.00 inch-ounces
Maximum Stop Torque:
56.00 inch-ounces
Nonturn Device Location:
At 3 oclock
Nonturn Device Radius:

0.313 inches

NSN 5905-01-184-1441

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Humidity proof and panel seal
Electrical Resistance Per Section:
2.000 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 251.0 and 318.0
Resistance Tempurature Characteristic Range Per Section In Percent:
-3.0/+0.0 -55 degrees celsius single section and -5.0/+10.0 -25 degrees celsius single section and -5.0/+10.0 25 degrees celsius single
section and +0.0/+3.0 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: