NSN 5905-01-184-3510

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-184-3510 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.010 **Overall Length:** 0.472 inches **Terminal Length:** 0.172 inches **Overall Height:** 0.250 inches **Overall Width:** 0.165 inches **Shaft Diameter:** 0.075 inches **Shaft Length:** 0.050 inches **Body Length:** 0.250 inches **Body Width:** 0.165 inches **Body Height:** 0.250 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 3600.0 and 9000.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Fragility Factor:**

Moderately rugged

Terminal Location:

Rear end

NSN 5905-01-184-3510

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Mounting Method: |
|--|
| Terminal |
| Cubic Measure: |
| 0.010 cubic inches |
| Electrical Resistance Per Section: |
| 10.000 percent, rated amperes c and better flooring |
| Rotary Actuator Travel In Angular Deg: |
| Between 3600.0 and 9000.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.100 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -100.0/+100.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.25 7th secondary quality |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |
| Clutch |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 85.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Test Data Document: |
| 81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 3 pin |
| Specification Data: |
| 81349-mil-r-39035/3 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |
| |