Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-184-5252

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-20.0/+20.0

#### **Electrical Resistance:**

1.500 kilohms

## **Resistance Tolerance In Percent:**

-1.000/+1.000

### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 25.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+275.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Type:**

# Wire lead

**Reactance Characteristic:** 

Inductive

Reliability Indicator:

Established

**Reliability Failure Rate Level In Percent:** 

0.001

#### **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.375 inches

#### **Body Length:**

1.780 inches

**Power Dissipation Rating In Watts:** 

10.000 free air

Cubic Measure (non-core):

0.196 cubic inches

#### **Unpackaged Unit Weight:**

13.000 grams

## Style Designator:

Axial terminal each end

## **Test Data Document:**

81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-39007/7 government specification

# Shelf Life:

N/a

# NSN 5905-01-184-5252

Wire Wound Fixed Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0