Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-184-6444

Section Quantity:

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.188 inches

**Body Length:** 

0.190 inches

**Body Width:** 

0.375 inches

Body Height:

0.375 inches

Actuator Type:

Flush drive with slot-hole

## Effective Electrical Rotation In Deg Angular Rotation:

270.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

**Center To Center Distance Between Terminals:** 

0.200 inches

**Terminal Location:** 

Lower adjacent side single row

#### **Mounting Method:**

Terminal

Cubic Measure:

0.026 cubic inches

**Electrical Resistance Per Section:** 

250.000 ohms c and better flooring

### **Rotary Actuator Travel In Angular Deg:**

300.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 7th secondary quality

# NSN 5905-01-184-6444 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 single section

## Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0