## NSN 5905-01-184-7969

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-184-7969

-100.0 to 100.0 Electrical Resistance: 1.100 magohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.00 to 160.0 Inclosure Method: Encaposulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating in Watts: 0.250 inches Royer Dissipation Rating in Watts: 0.250 inc	Tompurature Coefficient Of Registeres In Dam Box Dog Coloius
Electrical Resistance: 1.100 mapphms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.090 inches Body Length: 0.250 free air Unpackaged Unit Weight: 0.250 free air Unpackaged Unit Weight: 0.500 grams Stylo Designator: Axial terminal each end Test Data Document: 81349-mil+-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil+-39017/1 government specification Sheff Life: N/a	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
1.100 megohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 10.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.090 inches Rody Diameter: 0.090 inches Soly Diameter: 0.050 inches Power Dissipation Rating In Watts: 0.250 inches Soly Designator: Axial terminal each end Test Data Document: Style Designator: Axial terminal each end Test Data Document: sil 3494-milt-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: Sheff Life: No	
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Faiture Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 fine air Unpackaged Unit Weight: 0.250 fine air Unpackaged Unit Weight: 0.350 grams Style Designator: Axial terminal each end Test Data Document: Brita9-mil-1-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: Brita9-mil-1-39017/1 government specification Sheff Life: No	
-1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.250 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 organs Style Designator: Axial terminal each end Test Data Document: 81349-mill-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 814349-mill-39017/1 government specification Shelf Life: No	•
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  180.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent:  -0.001 Terminal Length: -1.500 inches Body Diameter: -0.0950 inches Body Length: -0.250 inches Power Dissipation Rating In Watts: -0.250 inches Power Dissipation Rating In Watts: -0.500 grams Style Designator: -Axial terminal each end Test Data Document: -B1349-milt-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: -B1349-milt-39017/1 government specification -Sheff Life: -No	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams Style Designator: Avial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Specification Data: 81349-mil-r-39017/1 government specification Shelf Life: N/a	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator: Established  Reliability Failure Rate Level In Percent:  0.001  Terminal Length: 1.500 inches  Body Diameter: 0.090 inches  Body Length: 0.250 inches  Power Dissipation Rating in Watts: 0.250 free air  Unpackaged Unit Weight: 0.500 grams  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-39017/1 government specification  Shelf Life:  N/a	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-390171 government specification Shelf Life: N/a	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.000 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.0250 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.3500 grams Style Designator: Axial terminal each end Test Data Document: 81349-milt-739017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milt-739017/1 government specification Shelf Life: N/a	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Faiture Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.250 inches Power Dissipation Rating In Watts: 0.250 fee air Unpackaged Unit Weight: 0.250 fee air Unpackaged Unit Weight: 0.3500 grams Style Designator: Axial terminal each end Test Data Document: 81349-milr-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-39017/1 government specification Shelf Life: N/a	
-55,0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Faiture Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 inches Tuppackaged Unit Weight: 0.500 grams Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-r-39017/1 government specification Shelf Life: N/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 Inches Body Diameter: 0.090 inches Body Diameter: 0.090 inches Body Length: 0.250 Inches Power Dissipation Rating In Watts: 0.250 inches Power Dissipation Rating In Watts: 0.500 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/1 government specification Shelf Life: N/a	-55.0 to 150.0
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/1 government specification Shelf Life: N/a	Inclosure Method:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/1 government specification Shelf Life: N/a	Encapsulated
Reliability Indicator: Established Reliability Failure Rate Level In Percent:  0.001 Terminal Length: 1.500 inches Body Diameter: 0.090 inches Body Diameter: 0.090 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.250 inches Power Dissipation Rating In Watts: 0.250 free air Unpackaged Unit Weight: 0.500 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/1 government specification Shelf Life: N/a	Terminal Type:
Established  Reliability Failure Rate Level In Percent:  0.001  Terminal Length: 1.500 inches  Body Diameter: 0.090 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.250 free air  Unpackaged Unit Weight: 0.500 grams  Style Designator: Axial terminal each end  Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-39017/1 government specification  Shelf Life: N/a	Wire lead
Reliability Failure Rate Level In Percent:  0.001  Terminal Length: 1.500 inches  Body Diameter: 0.090 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.250 free air  Unpackaged Unit Weight: 0.500 grams  Style Designator: Axial terminal each end  Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-39017/1 government specification  Shelf Life: N/a	Reliability Indicator:
Terminal Length:  1.500 inches  Body Diameter:  0.090 inches  Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.250 free air  Unpackaged Unit Weight:  0.500 grams  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-39017/1 government specification  Shelf Life:  N/a	Established
Terminal Length:  1.500 inches  Body Diameter:  0.090 inches  Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.250 free air  Unpackaged Unit Weight:  0.500 grams  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-39017/1 government specification  Shelf Life:	Reliability Failure Rate Level In Percent:
1.500 inches  Body Diameter: 0.090 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.250 free air  Unpackaged Unit Weight: 0.500 grams  Style Designator: Axial terminal each end  Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-39017/1 government specification Shelf Life: N/a	0.001
Body Diameter:  0.090 inches  Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.250 free air  Unpackaged Unit Weight: 0.500 grams  Style Designator:  Axial terminal each end  Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-39017/1 government specification  Shelf Life: N/a	Terminal Length:
Body Length: 0.250 inches  Power Dissipation Rating In Watts: 0.250 free air  Unpackaged Unit Weight: 0.500 grams  Style Designator: Axial terminal each end  Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-39017/1 government specification  Shelf Life: N/a	1.500 inches
Body Length:  0.250 inches  Power Dissipation Rating In Watts:  0.250 free air  Unpackaged Unit Weight:  0.500 grams  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-39017/1 government specification  Shelf Life:  N/a	Body Diameter:
O.250 inches  Power Dissipation Rating In Watts: O.250 free air  Unpackaged Unit Weight: O.500 grams  Style Designator:  Axial terminal each end  Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-39017/1 government specification  Shelf Life: N/a	0.090 inches
Power Dissipation Rating In Watts:  0.250 free air  Unpackaged Unit Weight:  0.500 grams  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-39017/1 government specification  Shelf Life:  N/a	Body Length:
Unpackaged Unit Weight:  0.500 grams  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-39017/1 government specification  Shelf Life:  N/a	0.250 inches
Unpackaged Unit Weight:  0.500 grams  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-39017/1 government specification  Shelf Life:  N/a	Power Dissipation Rating In Watts:
O.500 grams  Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-39017/1 government specification  Shelf Life:  N/a	0.250 free air
Style Designator:  Axial terminal each end  Test Data Document:  81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-39017/1 government specification  Shelf Life:  N/a	Unpackaged Unit Weight:
Axial terminal each end  Test Data Document:  81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-39017/1 government specification  Shelf Life:  N/a	0.500 grams
Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-39017/1 government specification  Shelf Life: N/a	Style Designator:
81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-39017/1 government specification  Shelf Life:  N/a	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data:  81349-mil-r-39017/1 government specification  Shelf Life:  N/a	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-39017/1 government specification  Shelf Life: N/a	81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Specification Data: 81349-mil-r-39017/1 government specification  Shelf Life: N/a	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Specification Data: 81349-mil-r-39017/1 government specification Shelf Life: N/a	
81349-mil-r-39017/1 government specification  Shelf Life: N/a	
Shelf Life: N/a	
N/a	
<del></del>	<del></del>

No

Demilitarization:

## NSN 5905-01-184-7969

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0