NSN 5905-01-185-5596

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-185-5596

Tempinature Coembrein On Nesistance in Primar Bog Celsius 3. Flectrical Resistance: 22.000 ob oma Resistance Tolerance in Percent: -2.000 to 2.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -5.5 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire laad Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Langth: 0.375 inches Power Dissipation Rating in Watts: 0.500 ree air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-739017 government specification of Shelf Life: Specification Data: 81449-mil-7390172 government specification (Shelf Life:)	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 20.000 obms Resistance Tolerance in Percent: 20.001 to 2000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 105.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 150.0 Inclosure Method: -55.0 to 150.0 Inclosure Method: -67.0 Tempurature Type: Wire lead Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Power Dissipation Rating in Watts: 0.375 inches Power Dissipation Rating in Watts: 0.300 free ai Unpackaged Unit Weight: 0.700 grams Style Designator: Avial terminal each end Test Data Document: 8149-mil-7-39017 specification (includes enginearing type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 8149-mil-7-39017/2 government specification	
22.00 2 .000 Resistance Tolerance in Percent: 2.00 12 .000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 18.00 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 10 15.00 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating in Watts: 0.376 inches Power Dissipation Rating in Watts: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mili-7-390173 government specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "spicial", "average", "", etc.). Specification Data: 81349-mili-7-39017/2 government specification	
Resistance Tolerance in Percent: -2.000 to 2.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating in Watts: 0.505 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Akial terminal each end Test Data Document: 81349-mili-7-390173 government specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data:	
2.000 to 2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating in Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-milt-739017/2 government specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification cervironmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Date: 81349-milt-739017/2 government specification	
Ambient Tempurature In Deg Celsius At Full Rated Power: 7.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 15.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-milt-739017/2 government specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification corwiromental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-milt-739017/2 government specification (
70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating in Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Diameter: 0.138 inches Body Diameter: 0.138 inches Body Diameter: 0.375 inches Power Dissipation Rating In Watts: 0.500 fire air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 15439-mill-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification erruin enruironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.0 to 15.0.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Diameter: 0.375 inches Power Dissipation Rating In Watts: 0.5500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 18149-mili-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mili-r-39017/2 government specification	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mill39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data:	
-5.0 to 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mili-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mili-r-39017/2 government specification (
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017/2 government specification in dest conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification in the conditions that are shown as "typical", "average", "", etc.).	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017/2 government specification Environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017/2 government specification Posicilication Data: 81349-mil-r-39017/2 government specification	
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification (environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Terminal Length: 1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
1.500 inches Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Body Diameter: 0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
0.138 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	·
0.375 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
0.500 free air Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017/2 government specification 1	
Unpackaged Unit Weight: 0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
0.700 grams Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Axial terminal each end Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Test Data Document: 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39017/2 government specification	
Specification Data: 81349-mil-r-39017/2 government specification	
81349-mil-r-39017/2 government specification	
Shelf Life:	
N/o	
N/a	
Unit Of Measure:	Unit Of Measure:
Demilitarization:	

No

NSN 5905-01-185-5596

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0