NSN 5905-01-185-9691

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-185-9691

Section Quantity:	
1	
Body Style:	
Rectangular	
Reliability Indicator:	
Established	
Reliability Failure Rate Level In Percent:	
0.100	
Terminal Length:	
0.200 inches	
Shaft Diameter:	
0.080 inches	
Shaft Length:	
0.090 inches	
Body Length:	
0.500 inches	
Body Width:	
0.100 inches	
Body Height:	
0.170 inches	
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Effective Electrical Rotation In Deg Angular Rotation:	
Between 1800.0 and 5400.0	
Maximum Starting Torque:	
2.00 inch-ounces	
Maximum Running Torque:	
2.00 inch-ounces	
Center To Center Distance Between Terminals:	
0.400 inches	
Terminal Location:	
Lower adjacent side single row	
Mounting Method:	
Terminal	
Cubic Measure:	
0.009 cubic inches	
Electrical Resistance Per Section:	
100.000 ohms c and better flooring	
Rotary Actuator Travel In Angular Deg:	
Between 1800.0 and 5400.0	

NSN 5905-01-185-9691

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between	Center Terminal And Outside Terminal:
0.100 inches	

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.3 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 pin

Specification Data:

81349-mil-r-39035/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0