## NSN 5905-01-186-0059

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-186-0059 **Section Quantity:** 1 **Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** 0.500 inches **Overall Height:** 0.797 inches **Overall Width:** 0.594 inches **Body Length:** 0.219 inches **Body Width:** 0.594 inches **Body Height:** 0.797 inches **Actuator Type:** Integral knob **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Fragility Factor:** Moderately rugged **Terminal Location:** Rear end **Mounting Method:** Tab **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 15.000 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:** 

260.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

## NSN 5905-01-186-0059

**Demilitarization:** 

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -150.0/+150.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 7th secondary quality **Resistance Tolerance Per Section In Percent:** -30.0/+30.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:**