NSN 5905-01-186-0060

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-186-0060 **Section Quantity:** 1 **Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** 0.500 inches **Overall Height:** 0.797 inches **Overall Width:** 0.594 inches **Body Length:** 0.219 inches **Body Width:** 0.594 inches **Body Height:** 0.797 inches **Actuator Type:** Integral knob **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Fragility Factor:** Moderately rugged **Terminal Location:** Rear end **Mounting Method:** Tab **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 51.000 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

NSN 5905-01-186-0060

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 7th secondary quality

Resistance Tolerance Per Section In Percent:

-30.0/+30.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0