Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-186-0060

## Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

#### **Overall Length:**

0.500 inches

#### **Overall Height:**

0.797 inches

#### **Overall Width:**

0.594 inches

#### Body Length:

0.219 inches

#### **Body Width:**

0.594 inches

## Body Height:

0.797 inches

# Actuator Type:

Integral knob

#### Effective Electrical Rotation In Deg Angular Rotation:

260.0

#### Maximum Starting Torque:

6.00 inch-ounces

#### Maximum Running Torque:

6.00 inch-ounces

#### Maximum Stop Torque:

48.00 inch-ounces

#### Fragility Factor:

Moderately rugged

#### **Terminal Location:**

Rear end

## Mounting Method:

Tab

## Features Provided:

Humidity proof

## **Electrical Resistance Per Section:**

51.000 percent, rated amperes c and better flooring

## Rotary Actuator Travel In Angular Deg:

260.0

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 7th secondary quality

**Resistance Tolerance Per Section In Percent:** 

-30.0/+30.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0