NSN 5905-01-186-0624

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-186-0624

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.188 inches
Shaft Diameter:
0.080 inches
Shaft Length:
0.060 inches
Body Length:
0.375 inches
Body Width:
0.190 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
1.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

NSN 5905-01-186-0624

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: