Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-186-5363

## Section Quantity:

1

Body Style:

Rectangular

## Reliability Indicator:

Not established

## Body Length:

0.196 inches

#### **Body Width:**

0.594 inches

**Body Height:** 

0.735 inches

Actuator Type:

#### Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

260.0

## Maximum Starting Torque:

7.00 inch-ounces

#### Maximum Running Torque:

2.00 inch-ounces

## Maximum Stop Torque:

48.00 inch-ounces

#### **Terminal Location:**

Lower adjacent side two rows

### Mounting Method:

Terminal

### **Electrical Resistance Per Section:**

10.000 kilohms single section

### **Rotary Actuator Travel In Angular Deg:**

260.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

### **Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

## **Actuator Travel Control Feature:**

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section



Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0