## NSN 5905-01-186-6693

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-186-6693

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
|--|
| -10.0/+10.0  |
| Electrical Resistance:   |
| 21.500 kilohms   |
| Resistance Tolerance In Percent:   |
| -1.000/+1.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 125.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 145.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -65.0/+145.0   |
| Inclosure Method:  |
| Encapsulated Encapsulated  |
| Terminal Type:   |
| Wire lead  |
| Reactance Characteristic:  |
| Noninductive   |
|  |
| Reliability Indicator:   |
| Established  Reliability Failure Rate Level In Bereent   |
| Reliability Failure Rate Level In Percent:   |
| 0.010  |
| Terminal Length: 1.500 inches  |
|  |
| Body Diameter:   |
| 0.250 inches   |
| Body Length:   |
| 0.500 inches   |
| Power Dissipation Rating In Watts:   |
| 0.150 free air   |
| Style Designator:  |
| Axial terminal each end  |
| Test Data Document:  |
| 81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-r-39005/4d government specification  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del>-</del>   |

No

Demilitarization:

## NSN 5905-01-186-6693

Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0